

Add : Town House Cordoba 59 Kamal Muara, Penjaringan, Jakarta Utara 14470

Tel : (021) 225 743 51 HP : +62 822 9888 9558

WWW.HANGCHA.CO.ID















FORK POSITIONER

PAPER ROLL CLAMP



HOW TO CHOOSE

- 1 Fork positioner option for 1.5ton-16ton.
- 2 4-spool hydraulic valves & 4 hose cycles will be needed.
- 3 Provide the mast type information of your current forklift.
- 4 More options, please refer to the product manual.

CHARACTERISTICS

- 1 Adjust the size between the forks according to the pallet size.
- 2 Forks can single move or simultaneously move.
- 3 Can be equipped with side shift function.




HOW TO CHOOSE


- Paper roll clamp option for 1.5T-10T.
- 2 4-spool hydraulic valves & 4 hose cycles will be needed.
- 3 Should provide material type, height, weight, diameter.
- 4 More options, please refer to the product manual.

CHARACTERISTICS

- 1 For different kinds of paper roll material.
- 2 Equipped with suitable armboard.
- 3 Optional function of rotate or side shift.
- 4 Short arm is fixed or adjustable, for smaller roller.


SPECIFICATION






| Capacity@ Load Center | Catalog Model No. | Adjusting Range | Width of Fork Carriage | Weight | Truck Mounting Class | Effective Trickness (ET) | Horizontal Center of Gravity (HCG) | Available Forklift |
|--------------------------|----------------------|-----------------|---------------------------|--------|----------------------------|--------------------------------|---|-----------------------|
| kg@mm | | mm | mm | kg | | mm | mm | t |
| 3500@500 | 3CS17G-00-1200 | 330-1120 | 1200 | 295 | III | 80 | 60 | 3-3.5 |

SPECIFICATION





| Capacity@ Max Diameter | Catalog Model No. | Opening Range | Mounting Class | Weight | Effective Trickness (ET) | Horizontal Center of Gravity (HCG) | Available Forklift | |
|---------------------------|----------------------|---------------|----------------|--------|--------------------------------|---|-----------------------|--|
| kg@mm | | mm | | kg | mm | mm | t | |
| 2000@1400 | 3CS2K-14 | 350-1400 | III | 735 | 200 | 225 | 3-3.5 | |

BALE CLAMP

PUSH AND PULL



HOW TO CHOOSE

- 1 Bale clamp option for 1.5T-10T.
- 2 4-spool hydraulic valves & 4 hose cycles will be needed.
- 3 Should provide material type, size, weight.
- 4 More options, please refer to the product manual.

CHARACTERISTICS

- 1 For different kinds of soft package.
- 2 Optional function of rotate or side shift.
- Widely used in the plant of cotton, waste paper, farm, chemical fiber, scrap iron.




HOW TO CHOOSE


- Push & pull option for 1.5T-3.5T.
- 2 4-spool hydraulic valves & 4 hose cycles will be needed.
- 3 Should provide push stroke, pallet goods size, weight.
- Saving slip sheet or side shifter function, should be noticed before ordered
- More options, please refer to the product manual.

CHARACTERISTICS

- Applicable in the industry of beer, beverage, chemical fertilizer, plastic particles, ceramic tiles and so on.
- Push and pull function in one control handle
- 3 Suitable in container load and unload.
- 4 Can equip with side shift function or slide paper stay or left.


SPECIFICATION







| Capacity@ Load Center | Catalog Model No. | Mounting Class | Opening Range | Arm Thickness | Arm Height (A) | Arm Lenght (B) | Frame Width (C) | Weight | Effective Trickness (ET) | Horizontal Center of Gravity (HCG) | Available Forklift |
|--------------------------|-------------------------|-------------------|------------------|------------------|-------------------|-------------------|--------------------|--------|--------------------------------|---|-----------------------|
| kg | | | mm | mm | mm | mm | | kg | mm | mm | t |
| 2500@500 | ES9B- BCS- 122B-J | III | 550-1880 | 65 | 465 | 1220 | 1038 | 565 | 170 | 390 | 3-3.5 |

SPECIFICATION







| Capacity@ Load Center | Catalog Model No. | Mounting Class | Stroke | Weight | Effective Trickness (ET) | Platen Size (LXW) | Outside Platen Spacing (C) | Horizontal Center Of Gravity (HCG) | Available Forklift |
|--------------------------|----------------------|-------------------|--------|--------|--------------------------------|----------------------|----------------------------------|---|-----------------------|
| kg@mm | | | mm | kg | mm | mm | mm | mm | t |
| 2000@600 | 3CS40-1211B-KL2 | III | 1200 | 605 | 272 | 1220×455 | 1015 or 1220 | 240 | 3.5 |

MORE ATTACHMENT OPTIONS Benefit from additional attachments to help the forklift do their job better.



