

Add : Town House Cordoba 59 Kamal Muara, Penjaringan, Jakarta Utara 14470

Tel: (021) 225 743 51 HP: +62 822 9888 9558









WWW.HANGCHA.CO.ID







# XF Series Diesel / Gasoline / LPG Counterbalanced Trucks

with capacities of 4,000 to 5,500kg



### **HANGCHA** be with you at every stage

Efficient, reliable solutions for your demands

### STAGE V & TIER 4F

With Hangcha you can meet all Stage V/Tier 4f emissions standards which provides customer demands for value, innovation and performance. The technologies include common rail fuel systems, diesel oxidation catalysts (DOC) and diesel particulate filters (DPF). Designed and optimised to every engine model, our forklift truck maximises efficiency and reliability.





Interactive instrument: The instrument adopts 4.0-inch color LCD display with four interactive buttons, and has one CAN bus communication function. The communication protocol is compatible with CANopen and SAE J1939 standards.

#### **HANGCHA Forklift with StageV and T4F**

| No. | Capacity | Series | Manufacturer | Engine         | Drive power | Model                              | Emission Std.         | Transmission | Power (kw/rpm) |
|-----|----------|--------|--------------|----------------|-------------|------------------------------------|-----------------------|--------------|----------------|
| 1   | 4.0-5.5t | XF     | KUBOTA       | V3307-CR-TIE5B | Diesel      | CPCD40/45-XW99BN,CPCD50/55-XXW99BN | Stage V / Tier4 final | OKAMURA      | 55.4/2200      |
| 2   | 4.0-5.5t | XF     | KUBOTA       | WG3800-L-E3C   | LPG         | CPYD40/45-XH11BN,CPYD50/55-XXH11BN | Stage V / Tier 3      | OKAMURA      | 61.6/2300      |
| 3   | 4.0-5.5t | XF     | XINCHAI      | 4E30YG52       | Diesel      | CPCD40/45-XH8BN,CPCD50/55-XXH8BN   | Stage V               | OKAMURA      | 55.8/2200      |

Note: Stage V applied for European Union also including Israel and Turkey Tier4 Final applied for North American





### **Reliability**

By focusing on enhancing reliability, reducing downtime, the XF series is able to make the greater productivity for customer.

XF series truck just equip with Okamura transmission. Brake drum and hub adopt monolithic construction.



Extra capacity combined radiator with serpentine wave and optimized heat dissipation channel enhance the heat dissipation capability to keep engine reliability even in heavy-duty applications.







XF series features rugged design, stamped frame and engine hood, stamped instrument panel and head guard, heavy profile rail mast combine to provide excellent rigidity, which ensures outstanding reliability even in heavy-duty work.

Bigger diameter of steering cylinder.

### **Productivity**

Dynamic load sensing hydraulic steering system, Efficiency lighting system, lower fuel consumption, combine to provide increased productivity and reduced operating costs.



The new Dynamic load sensing hydraulic steering system contributes to reduce loss of hydraulic and improve energy efficiency.



The new efficiency lighting system employs LED illuminant and new type reflector to reduce energy consumption, improve significantly illumination performance and prolong work time.

# **Comfortable Operation**

Optimal visibility in all directions create the best conditions for high productivity through relaxed and safe working.










The extra foot space is provided to reduce operator fatigue significantly. The new wide-open, non-slip step makes getting in and out easy and safe.

The optional Electro-hydraulic proportional control system contributes more sensitive and precise load handling. The easy-to-operate levers provide total load handling operation. An armrest is provided to reduce fatigue.



In addition to the soft landing system, the soft lifting system is adopted (front lifting cylinders of triplex mast and full free duplex mast), as a result, the noise and shock of the mast significantly decreases.



The developed front lifting cylinders with smaller outer diameter give the operator superior forward visibility.

The double front lifting cylinders provide better forward visibility.

In developing the new XF Series, comfort and ease of operation is carefully considered, for example, to improve vibration levels, compound engine damper and full floating power train are adopted.

Comfortable operating environments for operator also contribute to increased productivity.



In addition to rubber damper between frames and steering axle, compound engine damper and full floating power train achieve flexible connection between frames and driving system, as a result, traveling vibrations and vibrations from the driving system are significantly reduced.





The enlarged capacity of optimized exhaust muffler,the intake muffle and the noise shield technologies provide sig

- **1.** The new, relocated easy-to-see LCD meter lets the operator check on all aspects of operational status at a glance
- The new automobile-style light/turn-signal lever and forward-reverse lever are ergonomically designed and arranged to improve comfort and productivity.
- 3. The small diameter steering wheel with tilt adjustment provides the ideal operating position. The superior responsiveness of the steering wheel optimizes maneuverability even in parrow spaces.
- **4.** The parking brake is specially developed. The operational force is reduced by 30%
- The automobile-style suspended pedals provide more ergonomic operation.



### **Safety**

A wide range of technologies are applied to ensure absolute safety for both the operato and those in the surrounding.

An optional rear-pillar assist grip with a horn button enhances safety of operator while traveling in reverse.

The locking device of the engine hood damper and parking brake help add to safety.





- The operator presence sensing system incorporates lifting / tilting and traveling locking function, When the operator leaves the seat, the system automatically locks lifting / tilting and disables traveling to ensure safety.
- **2.** A throttling device is adopted to avoid the mast being out of control even some pipes are broken.

### **Easy Maintenance**

Careful design facilitates inspection and servicing. Easy maintenance reduces the amount of downtime and helps to reduce cost also.



The new vehicle controller integrates all electrical components, features excellent durability for temperature, water and vibration for most demanding operation.



CUMMINS engine use the special air filter, it can reduce air intake resistance dramatically, equipped with pressure alarm to masterthe maintaining time.





The cover on the Panel can be lifted up simply to check the brake fluid.

The easy-to-operate latch provides quick access to the engine compartment.

The two-piece design makes the floorboard easy to lift and remove for access to the power train.

The fasteners of the radiator cover can be turned easily by hand to enable quick inspections or servicing.

#### **Standards**

| Transmission              | Steering                          | Chassiss             | Control                         | Hydraulic                            |
|---------------------------|-----------------------------------|----------------------|---------------------------------|--------------------------------------|
| / Suspension transmission | / Full hydraulic power steering   | / Anti-slip pedal    | / Power steering                | / Dynamic load sending control valve |
| / Oil filter              | / Smaller diameter steering wheel | / Rubber pedal       | / Suspension pedal              | ( Diesel IC )                        |
| / Dipstick                | / Adjuster of steering wheel      | / Engine hood spring | / Integrated combination switch | / Hydraulic oil filter               |
| / Oil cooler              |                                   |                      | / Cable parking brake           | / Tilt cylinder self-lock valve      |
| / Non-asbesttos bake      |                                   |                      |                                 | / Hydraulic oil dipstick             |
| / Wet brake               |                                   |                      |                                 | / Dual pump                          |
| / OKAMURA transmission    |                                   |                      |                                 |                                      |

| Truck  |  | Electronics   | Mast  |   |
|--|--|---|---|---|
| / Traction device / Hand grip / Standard seat / Standard overhead guard / Waterproof cover on the guard / Back view mirror / Pneumatic tyres / Toolbox | / Counterweight net / Fan protector / Big capacity aluminum radiator / Whirlwind air cleaner / Safety filter / High-efficient intake muffler / High-efficient exhaust muffl / Upright exhaust pipe | / High-efficient front lights / High-efficient LED rear lights / Maintenance-free battery / Combination controller / LCD display / Neutual switch / Hour meter / Fuel gauge | / Water temperature gauge / Pre-heat indicator / Charging indicator / Oilpressure warning / Transmission oil pressure warning / Horn / Reversing buzzer | / Standard wide view duplex mast / Standard forks / Standard fork carriage / Standard load backrest / Mast speed limiting valve / Loading relieve valve / Softlanding system / Softlifting system / Side roller |

### **Options**

| Truck  | Transmission                     | Power  | Hydraulic   | Electronics  | Mast   |
|--|----------------------------------|--|---|--|--|
| / Cabin / Cabin heater / Front window / Super elastic tyre / Non-mark tyre(white/green) / Suspension seat / Extinguisher / Cover of tilt cylinder / Heightening overhead guard / Reversing assist grip / Customer painting / OPS(Operator Presence Sensing system) / Boot for tilt cylinder / Additional counterweight | / Dual driving tyre / Solid tyre | / DualfuelLPG system / Big capacity copper radiator / Upright exhaust system / Middle-positioned exhaust system / Dual air filter / Net cover of radiator / Sparkle arrester / Purified exhaust system / Swiwel LPG bottle support / Downward LPG bottle support | / Auxiliary hydraulic valve / Electro-hydraulic proportional control system / Return oil filter | / OBD / Front working light / Rear working light / Warning lamp / Speed meter / Over-speed alarm / LED working light | / Duplex wide view free-lift mast / Triplex wide view free-lift mast / Triplex wide view 4-cylinder free-lift mast / Special forks / Wider fork carriage / Widerload back rest |

### Optional Attachments

| / Paper roll clamp    | / Sideshifter         |
|-----------------------|-----------------------|
| / Rotating bale clamp | / Rotating forks      |
| / Load stabilizer     | / Fork extensioner    |
| / Multi-drum clamp    | / Load release device |
| / Bale clamp          | / Carton clamp        |
| / Drum clamp          | / Push-pull device    |
| / Dumping clamp       | / Bucket              |
| / Crane arm           | / Hook                |
| / String Pole         | / Lengthened fork     |











